


Twister™ Methods



Strip & seal linoleum - Standard

How to Strip & Seal Linoleum floor using Twister™ with a single disc machine.

Step 1:

Remove loose dirt from the floor. Carry out safety checks and mount the water tank.



Mount the driving disc with a Twister™ Red pad. Fill the tank with clean water (depending on the floors condition, a stripper product might be needed).

Step 2:

Start at the furthest point from the door/electricity plug. Apply the water with the single disc machine and scrub the surface working backwards in overlapping paths. Use a Red Twister™ – Utility pad for edges / borders.



Step 3:

Proceed scrubbing the surface with the single disc machine until the floor is free of any polymer / wax film.



Step 4:

Pick up the dirty water with a wet vacuum cleaner.




Step 5:

Once the floor is dry, matt the floor. Use a single disc machine with a dry Twister™ White pad to smooth the surface.



Step 6:

Remove dust afterwards using a damp mop or vacuum.



Step 7:

Pour acquired layers of sealer in a straight line onto the floor. Spread it evenly in lanes with a moist mop. At a distance of 1 to 1.5m redistribute the product across the lanes already applied.



Note! Follow manufacturer's recommendations.



Step 8:

Let it dry for 30-45 minutes between each layer as they are applied.



Step 9:

Apply additional layers of top coating. Spread it evenly in lanes with a moist mop. At a distance of 1 to 1.5m redistribute the product across the lanes already applied.



Step 10:

Let it dry for 30-45 minutes between each layer as they are applied.



Step 11:

Buff the floor using a Twister™ Green pad on a High-speed burnisher.



Note! After the upgrade is done the floor should be maintained with Green Twister™ during daily cleaning to preserve the cleanliness and shine.

“Please see the instruction for Daily cleaning....”.